

WEIHAO

SWITCHING POWER SUPPLY

伟豪开关电源

www.wehpower.com

MS-60W单组输出小体积电源
MS-60W Single output mini-size power supply**概述 Summary**

- > 单组输出：功率60W
Single output: power 60W
- > 输入电压：85 ~ 264VAC 120 ~ 370VDC
Input voltage: 85 ~ 264VAC 120 ~ 370VDC

**常见规格 General Specification**

111 x 78 x 36mm

性能 Specification	型号 Model	MS-60-5	MS-60-12	MS-60-15	MS-60-24
直流输出电压、电流 DC output voltage, current		5V 0~12A	12V 0~5A	15V 0~4A	24V 0~2.5A
纹波及噪音 Wave and noise		75mVp-p	100mVp-p	100mVp-p	100mVp-p
进线稳定性 Inlet wire stability		±0.5%	±0.5%	±0.5%	±0.5%
负载稳定性 Load stability		±1%	±0.5%	±0.5%	±0.5%
效率 Efficiency		80%	82%	82%	84%
直流电压可调节范围 Adjustable range for DC voltage		±10%	±10%	±10%	±10%
输入电压范围 Input voltage range		85 ~ 264VAC 120 ~ 370VDC 47 ~ 63Hz			
冲击电流 Impact current		冷启动电流 Cold start current	15A/115VAC	30A/230VAC	
过载保护 Overload protection		105% ~ 150% 切断输出, 自动恢复 105% ~ 150% cut off the output, automatic recovery			
过电压保护 Over voltage protection					
启动、上升、保持时间 Setup, rise, hold up time		200ms, 100ms, 20ms/230VAC 满载 at full load			
耐压性 Withstand voltage		输入输出间: 1.5kV 输入与外壳间: 1.5kV 输出与外壳间: 0.5kV 一分钟 I/P-O/P: 1.5kV I/P-FG: 1.5kV O/P-FG: 0.5kV 1minute			
隔离电阻 Isolation resistance		输入输出间 输入与外壳间 输出与外壳间: 500VDC/100MΩ I/P-O/P I/P-FG O/P-FG: 500VDC/100MΩ			
工作温度 Working temperature		-10°C ~ +50°C			
尺寸 Dimension		111 x 78 x 36mm			
重量 Weight		0.27kg			
包装 Packing		42 x 35 x 25CM/80PCS/21kg			

外形尺寸 Overall dimension(mm)

- 接线位置
- 端口1,2: 交流输入
- 端口3: 接地
- 端口4: 直流输出-V
- 端口5: 直流输出+V
- Terminal Pin No. Assignment
- Pin 1,2: AC Input
- Pin 3: GND
- Pin 4: DC output-V
- Pin 5: DC output+V

