

**WEIHAO**  
SWITCHING POWER SUPPLY

伟豪开关电源

www.wehopower.com

## S-350W单组输出电源 S-350W Single output power supply

### 概述 Summary

- > 单组输出：功率350W  
Single output: power 350W
- > 输入电压：90 ~ 132VAC/180 ~ 264VAC 由开关切换  
Input voltage: 90 ~ 132VAC/180 ~ 264VAC by switch



### 常见规格 General Specification

215 × 115 × 50mm

性能 Specification	型号 Model	S-350-5	S-350-9	S-350-12	S-350-15	S-350-18	S-350-24
直流输出电压、电流 DC output voltage, current		5V 0~50A	9V 0~38A	12V 0~29A	15V 0~23.3A	18V 0~19.4A	24V 0~14.6A
纹波及噪音 Wave and noise		150mVp-p	150mVp-p	150mVp-p	150mVp-p	150mVp-p	150mVp-p
进线稳定性 Inlet wire stability		±0.5%	±0.5%	±0.5%	±0.5%	±0.5%	±0.5%
负载稳定性 Load stability		±0.5%	±0.5%	±0.5%	±0.5%	±0.5%	±0.5%
效率 Efficiency		73%	78%	83%	83%	84%	85%
直流电压可调节范围 Adjustable range for DC voltage		±10%	±10%	±10%	±10%	±10%	±10%
输入电压范围 Input voltage range		90 ~ 132VAC/180 ~ 264VAC 由开关切换 254 ~ 370VDC 47 ~ 63Hz 90 ~ 132VAC/180 ~ 264VAC by switch 254 ~ 370VDC 47 ~ 63Hz					
冲击电流 Impact current		冷启动电流 Cold start current 25A/115VAC 50A/230VAC					
过载保护 Overload protection		105% ~ 135%切断输出，自动恢复 105% ~ 135% cut off the output, automatic recovery					
过电压保护 Over voltage protection		115% ~ 150%关闭输出，电源重启后可恢复输出 115% ~ 150% shut down O/P voltage, re-power on to recover					
启动、上升、保持时间 Setup, rise, hold up time		200ms, 50ms, 20ms/230VAC 满载时在满负载					
耐压性 Withstand voltage		输入输出间：1.5kV 输入与外壳间：1.5kV 输出与外壳间：0.5kV 一分钟 I/P-O/P: 1.5kV I/P-FG: 1.5kV O/P-FG: 0.5kV 1minute					
隔离电阻 Isolation resistance		输入输出间 输入与外壳间 输出与外壳间：500VDC/100MΩ I/P-O/P I/P-FG O/P-FG: 500VDC/100MΩ					
工作温度 Working temperature		-10°C ~ +50°C					
尺寸 Dimension		215 × 115 × 50mm					
重量 Weight		1kg					
包装 Packing		45.5 × 31.5 × 26CM/20PCS/20kg					

### 外形尺寸 Overall dimension(mm)

- ☐ 接线位置
- ☐ 端口 6,9：交流输入
  - ☐ 端口 7：接地
  - ☐ 端口 4,5,8：直流输出-V
  - ☐ 端口 1,2,3：直流输出+V
- ☐ Terminal Pin No Assignment
- ☐ Pin 6,9：AC input
  - ☐ Pin 7：GND
  - ☐ Pin 4,5,8：DC output-V
  - ☐ Pin 1,2,3：DC output+V

