

201W单组 201W Single output power supply

概述

- >单组输出: 功率200W
single output: 200W
- >输入电压: 110/220VAC ± 20% 由拨动开关选择
input Voltage range: 110/220VAC ± 20%
selectable by switch



常见规格 General Specification

215 × 115 × 50mm

性能Specification	型号Model	S-201-5	S-201-12	S-201-36	S-201-48
直流输出电压、电流 DC output		5V 40A	12V 16.5A	36V 5.6A	48V 4.2A
纹波及噪音 Wave and noise		120mVp-p	150mVp-p	150mVp-p	150mVp-p
进线稳定度 Inlet stability		± 0.5%	± 0.5%	± 0.5%	± 0.5%
负载稳定度 Load stability		± 1%	± 0.5%	± 0.5%	± 0.5%
效率 Efficiency		78%	80%	83%	84%
直流电压可调范围 Adjustable range for DC voltage		± 10%	± 10%	± 10%	± 10%
输入电压范围 AC input voltage range		85~132VAC/170~264VAC 由开关选择 47~63Hz,240~370VDC 85~132VAC/170~264VAC Selected by switch 47~63Hz,240~370VDC			
冲击电流 AC Inrush current		冷启动电流 25A/115V 50A/230V Cold-start current 25A/115V 50A/230V			
过载保护 Overload protection		105%~135%切断输出, 自动恢复 105%~135% hiccup mode, auto-recovery			
过电压保护 Over-voltage protection		115%~145% rated output voltage			
启动、上升、保持时间 Setup, rise ,hold up, time		200ms, 100ms, 20ms			
耐压性 Withstand voltage		输入输出间: 1.5KvAC 输入与外壳间: 1.5Kv 输出与外壳间: 0.5Kv 一分钟 I/P-O/P:1.5KvAC, I/P-FG:1.5Kv, O/P-FG:0.5Kv, 1minute			
隔离电阻 Isolation resistance		输入输出间 输入与外壳间 输出与外壳间: 500VDC/100MΩ I/P-O/P, I/P-FG, O/P-FG: 500VDC/100MΩ			
工作温度 Working temperature		-10°C~+50°C			
安全标准 Safety standards		符合GB4943, UL60950,EN60950 Design refer to GB4943,UL60950,EN60950			
EMC标准 EMC standards		符合GB9254, EN55022 等级B Design refer to Gb9254, EN55022, classB			
重量 Weight		0.9kg			

外形尺寸 Overall dimension(mm)

